



225

16/2 Speaker Cable CMR

Audio, Control, and Low Voltage Power

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	
CONDUCTOR PARAMETER	-
• Number of Conductors	2
• AWG Size	16
• Conductor Stranding	19x29
• Conductor Type	Bare copper
• Nominal DCR	4.2 Ohm/1000ft
• Cabling Lay Length	4 in
• Twists/Foot	3 twist/ft
INSULATION PARAMETER	
• Insulation Type	Thermoplastic
• Insulation Thickness	0.008 in
• Insulation Color Code	1. Black 2.Red
SHIELDING PARAMETER	
• Shield Type	None
ELECTRICAL CHARACTERISTICS	

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	PVC
Jacket Thickness	0.017 in
Nominal Cable O.D.	0.182 in
Plenum	No
NEC UL Rating	CMR, CMG
RoHS Compliant	Yes
Pull Tension	59 lbs
Bend Radius	1.638 in
Cable Weight	28 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	UL1666 Vertical Shaft
CSA Flammability	FT4
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



225

16/2 Speaker Cable CMR

Related Products

RELATED PRODUCTS	
Plenum Number	25225B
Aquaseal Number	AQC225
Aquaseal Direct Burial Number	AQ225
SpeakOn Panel Mount	CN-NL4MP