

**25240B**

22/4 Solid Unshielded CMP
 Audio and Control

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	4
• AWG Size	22
• Conductor Stranding	Solid
• Conductor Type	Bare copper
• Nominal DCR	17.5 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Polymer Alloy PVC
• Insulation Thickness	0.007 in
• Insulation Color Code	1.Black,2.Red,3.White,4.Green
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	Flexible Plenum
Jacket Thickness	0.015 in
Nominal Cable O.D.	0.136 in
Plenum	Yes
NEC UL Rating	CMP
RoHS Compliant	Yes
Pull Tension	34 lbs
Bend Radius	1.3 in
Cable Weight	17 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	NFPA 262 Plenum
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300



25240B

22/4 Solid Unshielded CMP
Audio and Control

Related Products

RELATED PRODUCTS	-
Non-Plenum Number	240
Aquaseal Number	AQC240