

**25244B**

18/4 UTP CMP

Audio, Control, and Low Voltage Power

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	
CONDUCTOR PARAMETER	
• Number of Conductors	4
• AWG Size	18
• Conductor Stranding	7x26
• Conductor Type	Bare copper
• Nominal DCR	6.2 Ohm/1000ft
• Cabling Lay Length	3.5 in
• Twists/Foot	3.4 twist/ft
INSULATION PARAMETER	
• Insulation Type	Plenum PVC
• Insulation Thickness	0.008 in
• Insulation Color Code	1.Black,2.Red,3.White,4.Green
SHIELDING PARAMETER	
• Shield Type	None
ELECTRICAL CHARACTERISTICS	

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	Flexible Plenum
Jacket Thickness	0.015 in
Nominal Cable O.D.	0.18 in
Plenum	Yes
NEC UL Rating	CMP
RoHS Compliant	Yes
Pull Tension	80 lbs
Bend Radius	1.61 in
Cable Weight	32 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	NFPA 262 Plenum
Operating Range	-0 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



25244B

18/4 UTP CMP
Audio, Control, and Low Voltage Power

Related Products

RELATED PRODUCTS	
Non Plenum Number	244
Aquaseal Direct Burial Number	AQ244