

**25272B**

22/10 Unshielded CMP
 Audio and Control

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	10
• AWG Size	22
• Conductor Stranding	7x30
• Conductor Type	Bare copper
• Nominal DCR	17 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Plenum PVC
• Insulation Thickness	0.007 in
• Insulation Color Code	1.Black,2.Red,3.White,4.Green,5. Brown,6.Blue,7.Orange,8.Yellow,9.Purple,10.Gray
SHIELDING PARAMETER	-
• Shield Type	None
ELECTRICAL CHARACTERISTICS	-

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	Flexible Plenum
Jacket Thickness	0.015 in
Nominal Cable O.D.	0.213 in
Plenum	Yes
NEC UL Rating	CMP
RoHS Compliant	Yes
Bend Radius	1.917 in
Cable Weight	36 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	NFPA 262 Plenum
Operating Range	-0 to 60 Deg C
UL Voltage Rating	300



25272B

22/10 Unshielded CMP
Audio and Control

Related Products

RELATED PRODUCTS	-
Non Plenum Number	272