

734D2 Coax - 734D Series

For more Information
please call

1-800-Belden1

**General Description:**

20 AWG solid .032" (.81mm) silver-plated copper conductor(s), gas-injected FHDPE insulation, Beldfoil® tinned copper braid shield (85% cverage), overall PVC jackets. (2) of these coax Siamese bonded in parallel.

Physical Characteristics (Overall)**Conductor****AWG:**

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
2	20	Solid	SPC - Silver Plated Copper	.032

Total Number of Conductors:

2

Insulation**Insulation Material:**

Insulation Material	Dia. (in.)
Gas-injected FHDPE - Foam High Density Polyethylene	.148

Outer Shield**Outer Shield Material:**

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
2		Braid	TC - Tinned Copper	85

Outer Jacket**Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter:

0.235 x 0.485 in.

Mechanical Characteristics (Overall)

Operating Temperature Range: -40°C To +75°C

UL Temperature Rating: 60°C

Non-UL Temperature Rating: 75°C

Bulk Cable Weight: 61 lbs/1000 ft.

Max. Recommended Pulling Tension: 120 lbs.

Min. Bend Radius/Minor Axis: 2.500 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification: CMR

CEC/C(UL) Specification: CMG

EU Directive 2011/65/EU (RoHS II): Yes

EU CE Mark: No

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/01/2004

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MIL Order #39 (China RoHS): Yes

Detailed Specifications & Technical Data



ENGLISH MEASUREMENT VERSION

734D2 Coax - 734D Series

Other Specification: Telcordia Specification GR-139-CORE

Flame Test

UL Flame Test: UL1666 Vertical Shaft

CSA Flame Test: FT4

Suitability

Suitability - Indoor: Yes

Plenum/Non-Plenum

Plenum (Y/N): No

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)

75

Nom. Inductance:

Inductance (µH/ft)

.097

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)

16.8

Nominal Velocity of Propagation:

VP (%)

80

Nominal Delay:

Delay (ns/ft)

1.27

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

10

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

2.4

Max. Operating Voltage - UL:

Voltage

300 V RMS

Other Electrical Characteristic 1: Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 OHM fixed bridge and termination.

Other Electrical Characteristic 2: RL tested in accordance with ASTM D-4566 paragraph 45.3, using a 75 OHM fixed bridge and termination.

Minimum Return Loss:

Description	Freq. (MHz)	Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
		5	95	30

Sweep Test

Sweep Testing: 100% Sweep Tested 15 - 95 MHz

Notes (Overall)

Notes: Siamese versions feature zip cord design with printing on one leg.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
734D2 0081000	1,000 FT	63.000 LB	GRAY	C	#20 GIFHDLDP SH PVC DUAL
734D2 0084000	4,000 FT	252.000 LB	GRAY		#20 GIFHDLDP SH PVC DUAL
734D2 008500	500 FT	34.500 LB	GRAY		#20 GIFHDLDP SH PVC DUAL

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 3 Revision Date: 08-05-2013

© 2016 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.