## **RCI Switches**



### 915 Passive Infrared

Hands-free egress switch. 6-1/4"W x 1-13/32"H x 1-1/2"D (159mm x 36mm x 38mm)



- Field-Selectable 12/24VDC
- 38mA max at 24VDC, 35mA at 12VDC
- · Hands free release for electromagnetic locks
- · Ideal for "request to exit" with electromagnetic locks
- · Adjustable setting for precise detection area desired
- · Adjustable-relay latch time delay (2-60 sec)
- Two Form C relays (rated 2A at 30VDC)
- SPDT switch configuration
- · Available in Gray or Black

#### **How To Order**





# 915AFI Active Focused Infrared

6-7/8"W x 1-7/8"H x 2"D (175mm x 48mm x 51mm)



- Mounts on or above the door frame with infrared beam directed near door hardware for pinpoint accuracy and operation, preventing circumvented entry by sliding objects under the door.
- Multiple relocking modes for any timed or door position conditions
- Relay output consists of two Form "C" contacts for NO/NC wiring
- Integrated local sounder with adjustable volume and activation LEDs
- 3 additional auxiliary inputs: request to exit, card reader and a door position switch
- 12 to 24 VDC/VAC
- Black finish
- · Certifications: UL 294/ULC S319

#### **How To Order**

915AFI x B