

Product Catalog.

CELLULAR COVERAGE SOLUTIONS FOR
HOME/OFFICE & VEHICLES



Cables and Connectors



RG11
COAX CABLE
F-MALE / F-MALE
BLACK

951127 2 feet 951100 100 feet
951150 50 feet 951155 500 feet
951175 75 feet¹

¹compatible with crimp connector 971150. Center pin from connector. Must be soldered onto cable.



RG6
LOW-LOSS COAX CABLE
F-MALE / F-MALE
WHITE

950602 2 feet
950620 20 feet
950630 30 feet
950650 50 feet



WILSON400
ULTRA LOW-LOSS COAX CABLE²
N-MALE / N-MALE BLACK

952302 2 feet 952360 60 feet
952310 10 feet 952375 75 feet
952320 20 feet 952300 100 feet
952330 30 feet 952305 500 feet
952350 50 feet 952301 1000 feet

²equivalent to LMR-400



RG58 LOW-LOSS FOAM COAX CABLE
SMA-FEMALE / SMA-MALE BLACK

955805 5 feet
951147 10 feet
955815 15 feet

SMA-FEMALE / SMA-MALE WHITE
955823 20 feet

N-MALE / SMA-MALE BLACK

955802 2 feet 955822 20 feet
955812 10 feet



RG58U
LOW-LOSS FOAM COAX CABLE
N-MALE / N-MALE BLACK
951134 2 feet

EXTENSION CABLE
SMA-MALE / SMA-FEMALE
955832 30 feet



RG174 CABLE
SMA-MALE / SMA-MALE BLACK
951151 3 feet

RG174 EXTENSION CABLE
SMA-MALE / FME-FEMALE BLACK
951144 6 feet




RG58U
LOW-LOSS FOAM COAX CABLE
N-MALE / N-MALE WHITE
951148 20 feet



FLAT WINDOW CABLE
F-FEMALE / F-FEMALE
WHITE

951152 8 inch
951177 10 inch



COAX CABLE BLACK

SMA-MALE TO SMA-MALE
951141 6 feet

SMA-FEMALE TO SMA-MALE
951130 6 feet

		LOSS PER 10'		
		800 MHz	1900 MHz	
ACTUAL SIZE	 13/32"	Wilson 400	.45 dB	.7 dB
	 13/32"	RG-11	.45 dB	.8 dB
	 3/8"	RG-6	.83 dB	1.35 dB
	 3/16"	RG-58	1.0 dB	2.66 dB
	 3/32"	RG-174	3.58 dB	6.66 dB