Product data sheet Characteristics

APCRBC105

APC Replacement Battery Cartridge #105 with 2 Year Warranty







Lead time	Usually in Stock	



Main

Product or Component Type	Replacement battery cartridge	
Number of cables	1	
Battery Type	Lead-Acid battery	
Provided Equipment	All required connectors	
	Battery recycling guide	
	Metallic battery tray or enclosure	
	Reusable packaging	
	Installation guide	

Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Enclosed battery cartridge
Battery Voltage	48V
Additional information	The SUA48RMXLBP3U requires two(2) APCRBC105
RBC Quantity	1

Physical

Height	4.25 in (10.8 cm)	
Width	6.50 in (16.5 cm)	
Depth	22.52 in (57.2 cm)	
Net Weight	54.12 lb(US) (24.55 kg)	
Mounting Mode	Not rack-mountable	

Environmental

Ambient Air Temperature for Operation	32104 °F (040 °C)
Operating altitude	010000 ft
Relative Humidity	095 %
Ambient Air Temperature for Storage	23113 °F (-545 °C)
Storage altitude	050000 ft (0.0015240.00 m)
Storage Relative Humidity	095 %
Storage Relative Humidity	095 %

Ordering	and	ship	pind	ı detail	S

GTIN	731304248729	
<u> </u>	.0.00.12.10.120	
Packing Units		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	10.98 in (27.9 cm)	
Package 1 Width	12.24 in (31.1 cm)	
Package 1 Length	29.02 in (73.7 cm)	
Package 1 Weight	58.11 lb(US) (26.36 kg)	
Offer Sustainability		
Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	
Take-back	Take-back program available	
Contractual warranty		
Warranty	2 years repair or replace	