Product data sheet Characteristics

APDU10151ME

APC NetShelter Rack PDU Advanced, Metered, 5.0kW, 1Phase, 208V, 30A, L6-30P, 40 Outlet





Overview

Lead time	Usually in Stock	

Main

hase
-30P
0 m)
E-T SE-T

Physical

Color	Black
Height	58.66 in (149.0 cm)
Width	2.20 in (5.6 cm)
Depth	2.95 in (7.5 cm)
Net Weight	14.55 lb(US) (6.6 kg)
Mounting Location	Side
Mounting preference	No preference
Mounting Mode	Rack-mounted
Mounting position	Vertical

Input

Line Rated Current	24 A	
Permissible voltage	200240 V	
Input current limits	30 A	
Load Capacity	4992 VA	
Input Frequency	50/60 Hz	

Output

Number of power socket outlets	20 C13/C15/C19/C21 20C13/C15	
--------------------------------	---------------------------------	--

Conformance

Product Certifications	TAA compliance	
Standards	UL 62368-1 CSA C22.2 No 62368-1	
ID D	FCC part 15 Subpart B	
IP Degree of Protection	IP44	

Environmental

Ambient Air Temperature for Operation	23140 °F (-560 °C)
Relative Humidity	595 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	595 %
Storage altitude	050000 ft (0.0015240.00 m)

Ordering and shipping details

	•		
G1	ΓΙΝ	731304439769	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	67.72 in (172 cm)	
Package 1 Width	4.57 in (11.6 cm)	
Package 1 Length	8.19 in (20.8 cm)	
Package 1 Weight	18.96 lb(US) (8.6 kg)	

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty 3 years repair or replace	
------------------------------------	--