



NOTES:

1. MATERIAL:
BODY - COPPER
SCREW - STEEL, ZINC PLATED
2. cULus LISTED FOR USE UP TO 600V & TEMPERATURE
RATED 90°C
3. RATED FOR USE WITH COPPER STRANDED CODE
CONDUCTOR ONLY
4. THESE PARTS ARE ROHS COMPLIANT
5. SEE PACKAGING LABEL FOR TIGHTENING TORQUE
INFORMATION
6. PKG QTY:
Q = 25
3 = 3



PANDUIT PART NUMBER	WIRE RANGE COPPER	CURRENT RATING (AMPS)	STUD SIZE IN	DIMENSIONS - IN [mm] +/- .02 [.5]						HEX SIZE*
				A	W	G	S	C	T	
CD35-36SL-QY	#14 - #6 (1) #10 & (1) #12 (1) #12 & (1) #14 (2) #10 (2) #12 (2) #14	50	3/16	2.13 [54.1]	.38 [9.7]	.22 [5.6]	1.00 [25.4]	.38 [9.7]	.07 [1.8]	SLOTTED
CD70-14SL-QY	#8 - #2	90	1/4	2.26 [57.4]	.50 [12.7]	.25 [6.4]	1.00 [25.4]	.38 [9.7]	.08 [2.0]	SLOTTED
CD125-14SL-QY	#2 - #1/0	125	1/4	2.94 [74.7]	.62 [15.7]	.44 [11.2]	1.00 [25.4]	.44 [11.2]	.11 [2.8]	SLOTTED
CD225-56HKR-Q	#2 - #4/0	225	5/16	3.38 [85.9]	.99 [25.1]	.50 [12.7]	1.00 [25.4]	.63 [16.0]	.13 [3.3]	7/32
CD300-38HK-3Y	#1 - 350	300	3/8	4.94 [125.5]	.99 [25.1]	.94 [23.9]	1.00 [25.4]	1.38 [35.1]	.12 [3.0]	5/16
CD400-38HK-3Y	#1/0 - 500	400	3/8	5.62 [142.7]	1.50 [38.1]	.94 [23.9]	1.75 [44.5]	.88 [22.4]	.18 [4.6]	5/16
CD650-12HK-3Y	600 - 1000	650	1/2	6.88 [174.8]	2.00 [50.8]	1.19 [30.2]	1.75 [44.5]	1.75 [44.5]	.25 [6.4]	3/8

*HEX STYLE & SIZE MAY DIFFER FROM CHART. DIFFERENCE IN SIZE WILL NOT AFFECT FIT, FORM, OR FUNCTION OF PART

							TITLE
							CD SERIES COPPER MECHANICAL CONNECTORS
							CUSTOMER DRAWING
						ITEM REVISION NAME N41666BA/00	
						DATASET FILE NAME N41666BA-DC/00.SLDDRW	
						UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm] .X ± .XXX ± .XX ± ANGLES ±	MATERIAL SEE NOTES
05	6/17	JHNU	JHNU	RGB	REVISED T DIMENSION FOR CD225-56HKR-Q: .13 WAS .12 REVISED TITLE BLOCK	N41666BA-C41666	DRAWING NUMBER C41666
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN	THIRD ANGLE PROJECTION  DRAWN BY JHNU DATE 3/06 CHK LEM SCALE XXXX SHEET 1 OF 1 SIZE B