

ACCESSORIES

SURVEILLANCE GRADE HARD DRIVES						ENTERPRISE HARD DRIVES						
Model												
	HK-HDD1T	HK-HDD2T	HK-HDD4T	HK-HDD6T	HK-HDD8T	HK-HDD10T	HK-HDD1T-E	HK-HDD2T-E	HK-HDD4T-E	HK-HDD6T-E	HK-HDD8T-E	HK-HDD10T-E
Capacity	1 TB	2 TB	4 TB	6 TB	8 TB	10 TB	1 TB	2 TB	4 TB	6 TB	8 TB	10 TB
Interface	SATA	SATA	SATA	SATA	SATA	SATA	SATA 6 Gb/sec.					
Classification	Audio/Video	Audio/Video	Audio/Video	Audio/Video	Audio/Video	Audio/Video	Audio/Video	Audio/Video	Audio/Video	Audio/Video	Audio/Video	Audio/Video
Operation	24/7 continuous	24/7 continuous	24/7 continuous	24/7 continuous	24/7 continuous	24/7 continuous	24/7 continuous	24/7 continuous				

HDD FOR STORAGE PRODUCTS		DVD-RW		HD-TVI MONITOR		HD-TVI CONVERTER		BALUN	
Model									
	HDD-SAS4T	HDD-SAS6T	HIK-DVDRW	DS-TT-X41T	DS-1H33	DS-1H18			
Description	HDD for, DS-A82024D, DS-AJ7824D	HDD for, DS-A82024D, DS-AJ7824D	DVD-RW option for NVR and DVR	Multifunction Video Tester, test a variety of video signals, including TurboHD, HDMI, CVBS, and VGA.	Converter from HD-TVI video signal to HDMI signal	Unshielded twisted pair (UTP) Baluns			

MICROSD CARD	
Model	
	HS-TF-H11/32G HS-TF-H11/64G HS-TF-H11/128G
Capacity	32 GB
NAND Flash	MLC
Form Factor	microSDHC/microSDXC
Read Speed	90/90/96 MB/s
Write Speed	46/28/44 MB/s
Operating Temperature	-25° C to 85° C (-13° F to 185° F)
Warranty (Year)	2
Product Highlight	<ul style="list-style-type: none"> • Read-Write Lock • Life Forewarning • Health Monitoring (With Hikvision Camera)

INTERNAL SSD	
Model	
	HS-SSD-V210/240G HS-SSD-V210/480G HS-SSD-V210/960G
Capacity	256 GB
NAND Flash	3D TLC
Form Factor	SATA III 6 Gb/s
Seq. Read (up to)	560 MB/s
Seq. Write (up to)	490/503/512 MB/s
Rnd. Read (up to)	73/83/87 K
Rnd. Write (up to)	25/22/17 K
Total Bytes Written (TBW)	200/400/800 TBW
MTBF (Hour)	1,500,000
Warranty (Year)	2
Product Highlight	<ul style="list-style-type: none"> • TBW is higher, more durable • Optimize for video surveillance

MICROPHONE		
Model		
	DS-2FP2020	DS-2FP4021-B
Type	HiFi Microphone	Digital Noise Reduction Microphone
Frequency Response	20Hz~20KHz	100Hz~16KHz
Pickup Range/Direction	70 m2 / 360°	60 m2 / 360°
Signal:Noise	60dB	75dB
Dynamic Range	70dB	85dB
Output Impedance	600 ohm unbalanced	600 ohm unbalanced
Connections	3 wires (Power, Audio Out, GND)	3 wires (Power, Audio Out, GND)
Construction	PVC	Aluminum alloy
Dimensions	Φ78 x 28 mm (3 x 1.1")	Φ64 x 20 mm (2.5 x 0.8")
Power Requirements (max.)	12V DC / 25mA	12V DC / 45mA