

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT PART NUMBER SYSTEM

HST 04 - 3 - Q 2 Y = INTERNAL CODE

COLOR:
NONE = BLACK
2 = RED

QUANTITY PER CARTON:
1 = 1 PCS
2 = 2 PCS
3 = 3 PCS
5 = 5 PCS
X = 10 PCS
Q = 25 PCS

LENGTH INCHES [mm]
3 = 3 [76.2]
6 = 6 [152.4]
9 = 9 [228.6]
12 = 12 [304.8]
48 = 48 [1,219.2]

EXPENDED I.D. TUBING

THICK WALL ADHESIVE LINED HEAT SHRINK TUBING

PANDUIT P/N	MIN. EXPANDED I.D. IN [mm]	MAX. RECOVERED I.D. IN [mm]	MIN. RECOVERED WALL THICKNESS IN [mm]
HST0.4-___(Y)	.400 [10.2]	.160 [4.1]	.08 [2.0]
HST0.8-___(Y)	.750 [19.1]	.220 [5.6]	.09 [2.3]
HST1.1-___(Y)	1.100 [27.9]	.375 [9.5]	.12 [3.0]
HST1.5-___(Y)	1.500 [38.1]	.500 [12.7]	.16 [4.1]
HST2.0-___(Y)	2.000 [50.8]	.666 [16.9]	.16 [4.1]
HST2.7-___(Y)	2.700 [68.6]	.870 [22.1]	.16 [4.1]
HST3.0-___(Y)	3.000 [76.2]	1.000 [25.4]	.16 [4.1]
HST3.5-___(Y)	3.500 [88.9]	1.200 [30.5]	.16 [4.1]

NOTES:

1. MATERIAL: CROSSLINKED POLYOLEFIN
2. COLOR: BLACK & RED
3. SHRINK RATIO: 3:1 (EXPENDED: RECOVERED ID)
4. SHRINK RATIOS ARE APPROXIMATIONS; PLEASE REFER TO DIMENSIONAL TABLE FOR THE EXACT MINIMUM EXPANDED AND MAXIMUM RECOVERED I.D.'S
5. "ALL WARRANTIES, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXCLUDED. (USER IS RESPONSIBLE TO DETERMINE SUITABILITY OF PRODUCT FOR INTENDED USE)."
6. DIMENSIONS IN BRACKETS ARE METRIC EQUIVALENT [mm]
7. SEE www.panduit.com FOR PACKAGE QUANTITIES INDICATED BY PART NUMBER SUFFIX.



REV						DESCRIPTION	ECN	DRAWN BY				DATE	CHK	SCALE	DRAWING NUMBER	
4	05-13-15	JBN	MRJS	RGRO	J. UPDATED DRAWING TO CURRENT STANDARDS	GB0239KM-DC	JVL				10-12-10	JVL	N.T.S.	SHT 1 OF 1		
						THICK WALL ADHESIVE LINED HEAT SHRINK (HST)				CUSTOMER DRAWING				SEE NOTES		
						ITEM REVISION NAME				G03597HN/00				DRAWING NUMBER: GB0239KM-DC		
						DATASET FILE NAME				G03597HN_DC_GB0239KM_04A				MATERIAL: SEE NOTES		
						UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]				THIRD ANGLE PROJECTION				DRAWING NUMBER: GB0239KM-DC		
						.x ± .05 [1.3] .xx ± .02 [.5]				.xxx ± .010 [.25] ANGLES ± 5 °				DRAWING NUMBER: GB0239KM-DC		
										THIRD ANGLE PROJECTION				DRAWING NUMBER: GB0239KM-DC		

D101000A/16