

Wall Mount Plug & Play Network Video Recorder

N4WNXL 4 Channel NVR with Built-In PoE+ Switch


Storage 1TB – 6TB

N4WNXL1TB	N4WNXL4TB
N4WNXL2TB	N4WNXL6TB
N4WNXL3TB	

IP



Patented Design



Key Features



EZ Wizards - For ease of use and setup

- Camera: quickly discover and install all Speco IP cameras
- Setup: for quick setup of general settings
- Network: network setup and port forwarding
- Record: quickly setup recording resolutions and recording type
- Search: quickly search for events from thumbnails
- Copy: quickly copy what you are playing onto a USB flash drive

- Up to 6MP resolution for recording and playback on all channels
- 80Mbps total available for camera recording bandwidth
- Built-in PoE+ (IEEE 802.3at) for all channels
- Supports H.264 compression
- **Free U.S.-Based DDNS Server Access**
- 5 year limited warranty²

Additional Features



- Plug & play feature with isolated traffic on the PoE ports with Speco's IP cameras
- Supports different recording types: Continuous, Motion, and Sensor
- Create bookmark pins on playback for easy reference
- Instant playback for individual channels directly from the live view screen
- Customizable channel view placement
- Network loss triggers automatic recording to SD card and automatic transfer back to NVR when network is restored¹

- Remote monitoring, recording, playback, configuration, upgrades, and PTZ control via the internet
- Simultaneous HDMI & VGA video output
- Built-in S.M.A.R.T technology (Self-Monitoring, Analysis and Reporting Technology for HDD)
- Supports 2-way audio communication (speaker required)
- Supports Digital Deterrent[®] which triggers audio message (pre-recorded or live) during an event (speaker required)
- Works with a majority of cameras that are conformant with ONVIF Profile S

Suggested Cameras



O4VLB5
4MP Bullet
IP Camera



O3VFBM
3MP Bullet
IP Camera



O3VFDM
3MP Dome
IP Camera



O4VLD5
4MP Dome
IP Camera

¹For supported IP camera models. ²Limited Warranty / Hard drives excluded. Check www.specotech.com for more details. iPhone is a trademark of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 10/03/18

Model		NXL	
Video	Input	Max. IP Channels	4
		Resolution	Max. 6MP
	Output	HDMI® / VGA	1920x1080, 1280x1024, 1280x720, 1024x768
		Split View	1, 4
Audio	Input	IP Camera (Network)	4
	2-Way Audio	Local	1 input (RCA), 1 output (RCA)
		Codec	G.711
Recording	Compression		H.264 (high, main, and baseline profiles)
	Resolution		Max. 6MP
	Bandwidth		Max. 80Mbps
	Recording Mode		Continuous / Motion / Sensor / Schedule / Manual
	Pre-Recording		Max. 30 seconds
	Post Recording		Max. 5 minutes
Playback	Search		EZ Search, Date/Time, Smart Search
	Multi-Decoding		1, 4
	Playback Speed		x1/16, x1/8, x1/4, x1/2, x1, x2, x4, x8, x16
Backup	Media		USB flash drive, USB HDD, Network
	File Format		Proprietary format, ASF, JPG
Storage	HDD	Interface	SATA II
		Capacity	6TB
		Internal Slots	1
	USB Ports		2 USB 2.0
Alarm	Sensor Input	IP Camera	4
Network	PoE		4 (IEEE 802.3at) PoE+
	Ethernet		10/100Base-T
	Throughput		Max. 48Mbps
	Protocols		HTTP, HTTPS, TCP/IP, IPv4, RTSP, UDP, DHCP, DNS, DDNS, SMTP, NTP
Network Access	Mobile Client		Speco One
	PC Web Viewer		Internet Explorer, Firefox
	MAC Viewer		Safari
	PC Client		SecureGuard® VMS
	Remote Setup and Upgrade		Supported
	User Access		Max. 128 users
Additional Features	Digital zoom, Daylight saving time, Email notification, NTP (network time protocol)		
Power	Power Supply		48VDC, 1.2A
	Total PoE Budget		50W
Environment	Operating Temperature		14°F – 131°F
	Relative Humidity		10% - 90% RH
Weight	Unit Weight (Gross Weight)		7.85 lbs.
Dimensions	Unit Dimensions (W x H x D)		11.5" (W) x 15" (H) x 3.5" (D)

Please note that specifications and unit exterior design are subject to change without notification.