


Intensifier IP® Full HD 1080p Indoor/Outdoor Dome IP Camera with Chameleon Cover™

O2iD4M 2.8-11mm auto iris varifocal motorized lens, dark grey housing

Features

- See color in low light without IR LEDs
- Motorized lens with auto focus
- Supports up to Full HD resolution @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- No problems caused by objects that reflect or absorb IR light sources
- With presets: Indoor, Outdoor, Elevator, Lobby, Hallway & Low Light
- Wide dynamic range (WDR) operation
- Supports H.264 and MJPEG codecs
- 2-way audio communication
- Micro SD card slot (card not included)
- Sensor input and relay output
- Built-in heater and anti-fog glass reduces condensation under any weather condition
- Chameleon Cover™: snaps on and can be painted to match any décor!*
- IP66 compliant
- ONVIF Profile S listed**
- 2 year warranty



Shown with included paintable, snap-on
*Chameleon Cover™

Camera Specifications

Image Sensor	Progressive scan 1/3" CMOS, 2.0MP
Maximum Resolution	1920 x 1080
Minimum Illumination	F1.2, Color: 0.001 lux (Max Intensify)
White Balance	ATW, Manual, Push
Exposure Control	Yes
Intensify	Selectable / Off
De-Fog	Yes
Backlight	WDR, BLC
DNR	3D (0-20)

Video Specifications

Main Resolution	1920x1080 @ 30fps
Compression	H.264 (HP/MP/BP), MJPEG
Bitrate Control	VBR, CBR
Multiple Streaming	5 profiles

Audio Specifications

Mono Input	64Kbps G.711 / 32Kbps G.726
Mono Output	64Kbps G.711

External Terminal Specifications

Ethernet	10/100 Mbps
Alarm	1 sensor input, 1 relay output
Video	Analog test output
Audio	1 mic in, 1 line out (3.5mm)
Power	DC jack
Storage	Micro SD slot

Network Specifications

Protocols	IPv4, TCP, UDP, RTP, RTSP, HTTP, HTTPS, SMTP, FTP, DHCP, UPnP, DNS
-----------	--

Free Apps with support for view on most smart devices

*Chameleon Cover™ - for best results when used outdoors, waterproof paint is recommended.**Visit www.specotech.com for latest ONVIF support. iPhone and iPad are trademarks of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 5/26/15



Network Specifications (continued)

DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP address filtering, digest authentication, user access log
User Access	8 simultaneous users at D1 resolution Number of users may vary depending on resolution

System Specifications

PoE	Standard (IEEE 802.3af)
Analytics	Motion detection (3 regions), audio detection
Alarm Triggers	Analytics & sensor input
Alarm Events	FTP video file upload, email image upload, micro SD card recording, relay out
Video Buffer	Configurable pre-record & post-record
Image Settings	Privacy mask

Client Specifications

Web Browser Support	Windows (Internet Explorer 8 and up, Chrome, Firefox)
PC Application	SecureGuard™ Plus

Operating & Unit Specifications

Power Supply	PoE, 12VDC (power supply not included)
Power Consumption	8W
Operating Temperature	-4° F - 122° F
Operating Humidity	8% - 80% RH
Unit Dimensions	3.62" (H) x 5.11" (Dia.)
Unit Weight	2 lbs.
Certifications	FCC, RoHS
Included in Package	Unit, CD (manual, software), mounting screws, L wrench

Optional Accessories



INTPM
Pendant
Mount



CVCJBD
Dome Camera
Junction Box



INTWM
Wall Mount



DFM
Tile Ceiling
Flush Mount



IPPOEINJ1295
12.95W
PoE Injector



PSW5
12VDC
Power Supply