


# OLS200

## Off-Line Switching Power Supply/Charger

### Description

Altronix OLS200 power supply/charger converts a 115VAC, 50/60Hz input into a 12VDC output. This unit has a wide range of applications for access control and security system accessories that require additional power.



OLS200

### Specifications

#### Input

Voltage 115VAC (working range 90VAC-132VAC), 50/60Hz, 1.9A.

#### Outputs

Voltage 12VDC.  
 Current 10A continuous supply current.  
 Other Short circuit and thermal overload protection. Filtered and regulated.

#### Back-up Battery (not included)

Type Sealed lead acid or gel type.  
 Failover Upon AC loss, instantaneous.

#### Supervision

AC Failure Form "C" contacts.  
 Battery Low/Fail Form "C" contacts.

#### Indicators (LED)

Input Input voltage is present.  
 DC Output Powered.

#### Agency Listings

CE European Conformity.

#### Physical and Environmental

Dimensions (L x W x H):  
 7.25" x 4.5" x 1.75" (184.1mm x 114.3mm x 44.5mm).

Product Weight 0.8 lb. (0.36 kg).

Shipping Weight 1.04 lb. (0.47 kg).

#### Temperature

Operating 0°C to 49°C (32°F to 120°F).

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

BTU/Hr (approx.): 61 BTU/Hr.

Mounting hardware included.


#### Lifetime Warranty

# OLS200

## Off-Line Switching Power Supply/Charger

### Board Dimensions (L x W x H) and Drawing

7.25" x 4.5" x 1.75" (184.1mm x 114.3mm x 44.5mm)



#### Lifetime Warranty