

P11VT3

APC Performance SurgeArrest 11 Outlet with
Phone (Splitter) and Coax Protection, 120V



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Cable length	8 ft (2.44 m)
Number of cables	1
Provided equipment	Coaxial cable Telephone Cable User Manual

Physical

Color	Black
Height	1.57 in (4 cm)
Width	4.69 in (11.9 cm)
Depth	11.89 in (30.2 cm)
Net Weight	2.34 lb(US) (1.06 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Input Frequency	50/60 Hz
Switching current capacity	15 A

Output

Number of power socket outlets	11
Outlet standard	NEMA 5-15R

Conformance

UL 1449 TVSS Rating	L-N: 400 L-G: 500 N-G: 500
Product Certifications	CSA
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$100000

Environmental

Ambient Air Temperature for Operation	5...113 °F (-15...45 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

Data Lines Protected (multi-line only)	1-4
NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	70 dB
Surge energy rating	3020 J

Ordering and shipping details

GTIN	731304249030
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.36 in (6 cm)
Package 1 Width	13.58 in (34.5 cm)
Package 1 Length	7.56 in (19.2 cm)
Package 1 Weight	2.98 lb(US) (1.35 kg)
Number of Units in Package 2	6
Package 2 Height	15 in (381.00 mm)
Package 2 Width	8 in (203.20 mm)
Package 2 Length	15 in (381.00 mm)
Package 2 Weight	19.58 lb(US) (8.88 kg)
SCC14	10731304249037

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

Contractual warranty

Warranty	Limited Lifetime
----------	------------------