

Gigabit Network PoE Switches

P4S6G


6-Port Gigabit Network Switch (4 ports PoE, 2 ports uplink)

P8S10G

10-Port Gigabit Network Switch (8 ports PoE, 2 ports uplink)

Features

- Gigabit performance on all ports (uplink and downlink)
- PoE watchdog mode: PoE will continuously monitor for lost device connections and reset the port when detected
- VLAN Mode:
 - When the VLAN mode is selected, each PoE port is isolated and independently connects with cameras, computers or other switches, while the uplink port connects with a router
 - The VLAN function helps avoid broadcast storms and ARP spoofing
- Surge Protection: Each port is equipped with a surge absorber, which can survive under 6,000V air ESD
- Port 1 supports 802.3bt 60W and all ports support 802.3at/802.3af
- All ports can be extended up to 800' (250M) @ 10MBPs using high quality CAT6 cable



Specifications	P4S6G	P8S10G
Downlink Ports	4 x 10/100/1000 Base-TX (PoE)	8 x 10/100/1000 Base-TX (PoE)
Uplink Ports	2 x 10/100/1000 Base TX	
Network Standards	IEEE 802.3/IEEE 802.3i 10BASE-T/IEEE 802.3u 100BASE-TX/IEEE 802.3x	
PoE Standards	IEEE 802.3af/at/PoE++	
Switch Capacity	10Gbps	20Gbps
Throughput	8.93Mpps	14.88Mpps
Exchange Type	Storage and Forwarding (full wire speed)	
MAC Address List	2K	2K
PoE Pin	af/at: 12 + 36-; af/at/poe++/bt: 12 + 45 + 36 - 78-	
PoE Output	Single port ≤ 30W (First Port Max 60W), Total for all ports ≤ 65W	Single port ≤ 30W (First Port Max 90W), Total for all ports ≤ 120W
Surge Protection	6KV (General), 4KV (Differential Mode), 8KV (ESD)	
Power Supply	Input AC: 100~240VAC 50-60Hz/ Output 57V 1.7A	Input AC: 100~240V 50-60Hz / Output 52V 2.3A
Power Consumption	Standby Power Consumption: ≤5W; Full-load Power Consumption: ≤65W	Standby Power Consumption: ≤8W ; Full-load Power Consumption: ≤120W
Operating Temperature	14 to 131 °F (-10 to 55 °C)	
Storage Temperature	-40 to 167 °F (-40 to 75 °C)	
Operating Humidity	5% - 90% (Non-condensing)	5% - 90% (Non-condensing)
Dimensions	(L x W x H): 7.5" x 5.1" x 1.4 (190mm x 130mm x 35mm)	(L x W x H): 8.3" x 5.9" x 1.4" (210mm x 150mm x 35mm)
Material	Metal	
Weight	1.32 Lbs. (0.6kg)	1.8 Lbs (0.8kg)

ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 12/1/22

Apps available from the following:



800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • specotech.com

