

Product data sheet

Specifications



APC Essential SurgeArrest 6 Rotating Outlets with 5V, 3.4A 2 Port USB Charger, 120V

PE6RU3

Overview

Lead time Usually in Stock

Main

Main Input Voltage 120 V
Input Connection Type NEMA 5-15P
Cable length 6 ft (1.83 m)
Number of cables 1
Provided equipment User Manual

Physical

Color Black
Height 12.83 in (32.6 cm)
Width 1.73 in (4.4 cm)
Depth 1.97 in (5 cm)
Product Weight 1.92 lb(US) (0.87 kg)
Mounting preference No preference
Mounting Mode Not rack-mountable

Input

Input power 1800 W
Maximum Line Current per phase 15 A
Input Frequency 50/60 Hz
Maximum Input Current per Phase 15 A
Switching current capacity 15 A

Output

Number of power socket outlets 6
Outlet standard NEMA 5-15R

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Conformance

Product Certifications	cULus
Standards	UL 498 UL 1310 UL 1449

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
EMI/RFI Noise rejection (100 kHz to 10 MHz)	40 dB
Peak current	48 kA common mode 24 kA normal mode
Surge energy rating	1080 J

Ordering and shipping details

GTIN	731304343691
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.37 in (36.5 cm)
Package 1 Width	2.24 in (5.7 cm)
Package 1 Length	4.13 in (10.5 cm)
Package 1 Weight	1.98 lb(US) (0.9 kg)
SCC14	10731304343698

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty

Limited Lifetime

Recommended replacement(s)