Product data sheet Characteristics

SBP3000RM

APC SERVICE BYPASS PDU, 120V 30AMP W/ (4) NEMA 5-20R AND (1) L5-30R



Overview

Lead time	Usually in Stock



Main

Main Input Voltage	120 V	
Product or Component Type	Bypass kit	
Main Output Voltage	120 V	
Input Connection Type	NEMA L5-30P	
Number of rack unit	2U	
Cable length	8 ft (2.44 m)	
Number of cables	1	
Provided Equipment	User Manual	
	Rack Mounting brackets	

Physical

Color	Black	
Height	3.50 in (8.9 cm)	
Width	17.01 in (43.2 cm)	
Depth	2.99 in (7.6 cm)	
Net Weight	9.81 lb(US) (4.45 kg)	
Mounting Location	Front	
Mounting preference	No preference	
Mounting Mode	Rack-mounted	

Input

Input Frequency	50/60 Hz	
Permissible voltage	100125 V	
Max line current	30 A	
Input current limits	30 A	
Load Capacity	3000 VA	
Load Power Factor Range	01	

Output

Maximum Total Current Draw per Phase	30 A
Number of power socket outlets	4 NEMA L5-20R 1 NEMA L5-30R
Number of power socket outlets	5
Protection Type	Circuit breaker
Cord Length	4 ft (1.22 m)
Efficiency	99 %

Conformance

Product Certifications	TÜV
------------------------	-----

Environmental

Ambient Air Temperature for Operation	32104 °F (040 °C)
Relative Humidity	095 %
Operating altitude	015000 ft
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage Relative Humidity	095 %
Storage altitude	050000 ft (0.0015240.00 m)

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304266723
Returnability	No
Country of origin	PH

Packing Units

PCE	
1	
5.94 in (15.1 cm)	
11.61 in (29.5 cm)	
18.23 in (46.3 cm)	
11.62 lb(US) (5.27 kg)	
	1 5.94 in (15.1 cm) 11.61 in (29.5 cm) 18.23 in (46.3 cm)

Offer Sustainability

EU RoHS Directive	Compliant EPEU RoHS Declaration	
-------------------	---------------------------------	--

Contractual warranty

Warranty	2 years repair or replace	