
Product data sheet Characteristics

SMT1500RM2UCUS

APC Smart-UPS, Line Interactive, 1500VA, Rackmount 2U, 120V, 6x NEMA 5-15R outlets, SmartConnect Port+SmartSlot, AVR, LCD, TAA







Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V	
Other Input Voltage	110 V	
, ,	125 V	
Main Output Voltage	120 V	
Other Output Voltage	110 V	
	125 V	
Input Connection Type	NEMA 5-15P	
Output connection type	6 NEMA 5-15R	
Provided equipment	CD with software	

Batteries & Runtime

Battery Charge Power (Watts)	144 W rated

Physical

Color Black	
-------------	--

Input

Efficiency at full load	75154 V adjustable
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Topology	Line Interactive	
Waveform Type	Sine wave	
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains	

Conformance

Comornance		
Product Certifications	cULus[RETURN]ENERGY STAR V2.0 (USA)	

Environmental

Relative Humidity	095 %
Storage Relative Humidity	095 %

Ordering and shipping details

GTIN 731304424420

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.25 in (23.5 cm)
Package 1 Width	24.02 in (61 cm)
Package 1 Length	23.23 in (59 cm)
Package 1 Weight	70.81 lb(US) (32.12 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	3 Years