




APC DIN Rail - Panel Mount UPS with High Temp Battery 500VA 230V

SUA500PDRI-H

Product availability: Non-Stock - Not normally stocked in distribution facility



Overview

Presentation	Proven Industrial UPS power protection for control applications and harsh environments.
Lead time	Usually in Stock

Main	
Main Input Voltage	230 V
Other Input Voltage	220 V
	240 V
Main Output Voltage	230 V
Other Output Voltage	220 V
	240 V
Kw Rating	325 W
Rated power in VA	500 VA
Product or Component Type	Uninterruptible power supply (UPS)
Output connector type	Hard Wire 3-wire (H N + E) 1
Battery Type	Lead-Acid battery
Provided equipment	CD with software
	Documentation CD
	Installation guide
	Smart UPS signalling RS-232 cable

Batteries & Runtime

Extendable Run Time	0
Included Battery Modules	1
Battery Slots Empty	1
Typical recharge time	2 h
RBC Quantity	1
Battery life	35 year(s)
Replacement battery	APCRBC136 ☐
Battery Charge Power (Watts)	60 W rated

General

Number of power module filled

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Number of power module free slots	0
Redundant	No

Physical

•	
Height	5.8 in (14.8 cm)
Width	14.3 in (36.2 cm)
Depth	6.7 in (17.1 cm)
Net Weight	28.35 lb(US) (12.86 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Efficiency at full load	151302 V adjustable 160285 V
Number of input connectors	1 Hard Wire 3-wire (1PH+N+G)
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Harmonic distortion	Less than 5%
Maximum configurable power in VA	500 VA
Max Configurable Power (Watts)	325 W
Topology	Line Interactive
Efficiency at full load	94 % full load)
Output Frequency (sync to mains)	4753 Hz for 50 Hz nominal sync to mains

Conformance

Product Certifications	CE VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic level	55 dBA
Online Thermal Dissipation	90 Btu/h
Operating altitude	010000 ft
Ambient Air Temperature for Operation	32122 °F (050 °C)
Ambient Air Temperature for Storage	5113 °F (-1545 °C)
Storage altitude	050000 ft (0.000000000015240.0000000000 m)
IP degree of protection	IP20
Relative Humidity	095 %

Communications & Management

Control panel	LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators
Emergency Power Off (EPO)	Yes
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone

Surge Protection and Filtering

Surge energy rating	540 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

Ordering and shipping details

Category	09305-INDUSTRIAL UPS
Discount Schedule	IUPS
GTIN	3606485441054
Returnability	No
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.7 in (29.7 cm)
Package 1 Width	11.7 in (29.7 cm)
Package 1 Length	18.9 in (48.1 cm)
Package 1 Weight	29.304 lb(US) (13.292 kg)

Contractual warranty

Warranty	2 years repair or replace	
----------	---------------------------	--

Sustainability Green Premium

Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >









Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

Energy Efficient Product



Take-Back Program Available

Well-being performance



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov