



### Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

### Main

Main Input Voltage	200 V 208 V
Product or Component Type	Power module
Other Input Voltage	240 V
Main Output Voltage	100 V 120 V 200 V 208 V
Other Output Voltage	240 V
Kw Rating	3200 W
Rated power in VA	4000 VA
Output connector type	Hard Wire 4-wire (2PH+N+G) 1
Number of rack unit	0U
Number of cables	1
Provided Equipment	Installation guide

### Batteries & Runtime

Included Battery Modules	0
Battery Slots Empty	0
Additional information	Configurable for 120/208 or 120/240 output voltage

### Physical

Color	Silver
Height	5.9 in (15 cm)
Width	9.8 in (25 cm)
Depth	22.2 in (56.5 cm)
Net Weight	33.07 lb(US) (15 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
USB compatible	No

## Input

Input Frequency	45...65 Hz auto-sensing
Efficiency at full load	155...276 V
Input Power Factor at Full Load	0.98

## Output

Max Configurable Power (Watts)	3200 W
Harmonic distortion	Less than 5 % at full load
Output Frequency (sync to mains)	47...63 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal not synced 60 Hz +/- 0.1 % for 60 Hz nominal not synced
Crest factor	Up to 5 : 1
Topology	Double Conversion Online
Wave type	Sine wave

## Conformance

Product Certifications	CSA
Standards	FCC Part 15 class A UL 1778

## Environmental

Ambient Air Temperature for Operation	32.0000000000...104.0000000000 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5.0000000000...113.0000000000 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...15000 ft (0.0000000000...4572.0000000000 m)
Acoustic level	62 dBA

## Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304218876
Returnability	No
Country of origin	PH

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.3 in (43.9 cm)
Package 1 Width	31.1 in (79 cm)
Package 1 Length	13.0 in (33 cm)
Package 1 Weight	40.08 lb(US) (18.18 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------