

TS300 Programmable Digital Timer



BASIC OPERATION

The Leviton Programmable Digital Timer (TS300) provides energy saving control of indoor incandescent and fluorescent lighting as well as motor loads such as fans and circulating pumps. The TS300 features two presets that can be used to comply with ASHRAE 90.1 and 2016 Title 24, Part 6 requiring:

- Two hour timing for countdown timer switch
- Four hour timing for ASHRAE 90.1

The TS300 uses a timed override feature to allow lights and HVAC to remain ON for a specified amount of time to accommodate after-hours crews. The aesthetically-pleasing timer is easy to install and can replace any wall switch.


APPLICATIONS

- Restrooms
- Storage rooms
- Supply closets
- Janitorial spaces
- Small office

FEATURES

- Zero arc point switching
- Wallplate locks access to dip switches for tamper resistance
- Backlit LED
- Optional audible blink warning
- No minimum load requirement
- Adjustable time delay and sensitivity
- Dual 120/277 VAC operation
- Can be used to comply with ASHRAE 90.1 and 2016 Title 24, Part 6 countdown timer switch requirements, IECC, UL and cUL listed

DIMENSIONS






PRODUCT DATA


LEVITON®

3-WAY WIRING DIAGRAM



4-WAY WIRING DIAGRAM

Use momentary switches at all loations



SPECIFICATIONS

SPECIFICATIONS		
ELECTRICAL		
Power	120/277VAC; 50/60Hz	
Load Rating	120VAC 15A Resistive 10A Ballast 1200W LED lamp driver 8A Tungsten 1/4 HP Motor 360VA Pilot duty	277VAC 15A Resistive 10A Ballast
ENVIRONMENTAL		
Operating Temperature Range	32 to 122°F (0 to 50°C)	
Relative Humidity	0-95%	
PHYSICAL		
Dimensions	4.2" (106.68mm) H x 1.8 (45.72mm) W x 1.65" (41.91mm) D	
Construction	High-impact, injection-molded plastic	
Color	White	
OTHER		
Listings	Can be used to comply with ASHRAE 90.1 and 2016 itle 24, Part 6 countdown timer switch requirements, IECC, UL and cUL listed	
Warranty	Five-year limited warranty	

ORDERING INFORMATION

CAT NO.	DESCRIPTION	
	120/277 VAC Digital Indoor Programmable Timer, wallplate included, White	

Leviton Manufacturing Co., Inc. Global Headquarters

201 North Service Road, Melville, NY 11747-3138 tel 800-323-8920 fax 800-832-9538 tech line (8:30AM-7:00PM ET Mon-Fri) 800-824-3005

Leviton Manufacturing Co., Inc. Energy Management, Controls and Automation

20497 SW Teton Avenue, Tualatin, OR 97062 tel 800-736-6682 fax 503-404-5594 tech line (6:00AM-4:00PM PT Mon-Fri) 800-959-6004