

VISTA-32FB

Commercial Partitioned Fire and Burglary Alarm Control Panel

Designed to integrate seamlessly with CCTV, access control and the Resideo full range of fire and burglary components, the VISTA-32FB provides the ultimate protection of life and property. The UL Listed commercial fire and burglary control panel supports up to two partitions and up to 32 zones/points using hardwired, wireless and V-Plex® addressable technologies. A diverse line of initiating devices, notification circuits, communication devices, keypads, RF receivers and relays are also supported. The VISTA-32FB has been designed to mount quickly and easily.



UL864 9th Edition Approved

FEATURES AND BENEFITS

- Supports addressable V-Plex access control points using VistaKey (up to 4 doors)
- Supports eight hardwired zones, 24 V-Plex addressable points/zones, or 32 wireless points/zones
- Can control two separate areas (partitions) independently
- Stores up to 512 events and can accommodate 75 user codes
- Easily programmed and maintained with newly upgraded Compass Downloader Software
- Automatic smoke detector sensitivity maintenance testing
- Commercial Wireless Fire and Burglary
- Notification Appliance Circuits (two):
 - Programmable
 - Individually silenceable
- Carbon monoxide (CO) zone support (Rev 5 and higher)
- Programmable on-board auxiliary relay
- False alarm reduction features:
 - Exit error logic
 - Exit delay reset
 - Cross zoning
 - Call waiting defeat
 - Recent close report
- Supports commercial hardwired, addressable V-Plex polling loop and wireless zones
- Listed to UL864 9th Edition (Rev 5 and higher)

VISTA-32FB

Commercial Partitioned Fire and Burglary Alarm Control Panel

ADDITIONAL FEATURES

- Hardwired zones
 - Provides nine style B hardwired zones
 - EOLR supervised for Fire and UL burglary installations
 - Supports N.O. or N.C. sensors
 - Individually assignable to one of eight partitions
 - Up to 16 two-wire smoke detectors each on zone one and two (32 total)
- Patented addressable V-Plex polling loop technology
 - Supports up to 24 two-wire V-Plex zones/points
 - Global polling technology for faster processing
 - Supervised by panel
 - Individually assignable to partitions, notification circuit (bell) output or aux relay
 - 4,000 ft. capability without the use of shielded cable
 - Extender/Isolation bus modules
- Two-wire smoke detector zone/group expansion module adds two or four zones
 - Eight zone – Class A and B extender module
 - Eight zone – Class B extender module
 - One zone supervised contact monitor module
- UL Listed wireless expansion
 - Supports up to 32 wireless zones/ points using 5881ENHC or 5883H Receiver
 - Supervised by control for check-in signals
 - Tamper protection for transmitters
 - Individually assignable up to eight partitions
 - Supports wireless smoke detectors
- Event reporting
- Local printer for access or VISTA related event

- Up to four doors using VistaKey V-Plex Access Control
- Stored events for one call retrieval
- Communication
 - Panel operation during download
 - Split/Dual Reporting

Applications

The VISTA-32FB control is well suited for a variety of applications as an integrated fire and burglary control. Some of the applications supported are: medical and professional buildings, churches or synagogues, office buildings, schools, strip malls, residences and factory or warehouse environments.

Installation

The VISTA-32FB alarm system has been designed to mount both quickly and easily. It meets all applicable requirements for UL commercial fire and burglary installations.

VISTA-32FB Technical Specifications

ELECTRICAL

Primary power: 18VAC @ 72VA ADEMCO No. 1451

Quiescent current draw: 300mA

Backup battery:

12VDC, 7AH min to 34.4AH max

Lead acid battery (gel type)

Alarm power: 12VDC, 1.7A max for each notification (bell) circuit output

Aux. standby pwr: 12VDC, 1A max

Total power: 2.3A at 12VDC, 3.4A at 24VDC from all sources

24 hours with 1A standby load

FUSING

Battery input, aux. and notification (bell) circuit outputs are protected using PTC circuit protectors. All outputs are power limited.

MAIN DIALER

Line seize: Double Pole

Ringer equiv.: 0.7B

Formats: ADEMCO Low Speed, ADEMCO 4+2 Express, ADEMCO High Speed, ADEMCO Contact ID, Sescoa and Radionics

CABINET DIMENSIONS

14.5" H X 12.5" W X 3" D

ENVIRONMENTAL

Storage temp: 14° F to 158° F
(-10° C to 70° C)

Operating temp: 32° F to 122° F
(0° C to 50° C)

Humidity: 85% RH

EMI: Meets or exceeds the following requirements:

- FCC Part 15, Class B Device
- FCC Part 68
- IEC EMC Directive

AGENCY LISTINGS

UL listed to:

UL 985: Household Fire Warning System Units

UL 864: Control Units and Accessories for Fire Alarm Systems

UL 1023: Household Burglar-Alarm System Units

UL 1610: Central-Station Burglar-Alarm Units

UL 365: Police Station Connected Burglar Alarm Units and Systems

UL 609: Local Burglar Alarm Units and Systems

UL 1635: Digital Alarm Communicator System Units

VISTA-32FB Compatible Devices

AUXILIARY DEVICES

- 4204 – Relay Module, four form C contacts
- 4204CF – Two supervised output circuits
- 5140DLM – Supervised Dialer
- 5881ENHC – Commercial Wireless Receiver
- 5883H – Wireless Transceiver
- 6160CR-2 – High Security Fire Alpha Keypad UL864 Rev 9 Listed
- 6160C – Custom Alpha Display Keypad (Resideo)

TWO-WIRE SMOKE DETECTORS

CONVENTIONAL

System Sensor
ESL
DSC

HORN/STROBES

System Sensor
Wheelock
Gentex

MANUAL PULL STATIONS

- 5140MPS-1
- 5140MPS-2

V-PLEX (ADDRESSABLE) DEVICES

- 4101SN Relay Zone Module
- 4190SN Remote Point Module – two zones
- 4193SN Two Zone Serial Interface Module
- 4208U Loop Expansion Module – eight zones
- 4208SNF Eight Zone/2 Class A/6 Class B Expander Module
- 4297 Isolator/Extender Module
- V-Plex VSI Isolator Module

V-PLEX SMOKE DETECTORS

- 5193SD
- 5193SDT

V-PLEX MOTION SENSORS/PIR

- IS3050A-SN
- DT8050A-SN

V-PLEX CONTACTS

- 4191SN-WH
- 4939SN-WH, 4939SN-BR, 4939SN-GY
- 4959SN

V-PLEX GLASSBREAK DETECTORS

- FG1625SN

COMMUNICATORS

- LTE-HSV LTE High Security Multi-Path Communicator
- LTE-CFA/CFV Commercial Fire Internet and LTE Communicator
- 7847i-E Enterprise Internet Communicator
- 7847i Internet Communicator

ACCESS CONTROL

VistaKey V-Plex (addressable) Access Control
VistaKey-SK Starter Kit
VistaKey-EX Expansion Kit

COMMERCIAL WIRELESS DEVICES

- 5808W3 – Photoelectronic Smoke/Heat Detector
- 5806W3 – Photoelectric Smoke Detector
- 5809SS – Wireless Heat Detector
- 5817CBXT – Wireless Commercial Transmitter
- 5869 – Hold-Up Transmitter

ORDERING

| | |
|---------|---|
| V32FBPT | Commercial Fire and Partitioned Burglary Alarm Platform |
| V32FB-9 | UL864 Rev 9 Version (Rev 5 and higher) |

For more information

resideo.com/pro



For more information
resideo.com

Resideo Technologies, Inc.

2 Corporate Center Drive,
Suite 100
P.O. Box 9040
Melville, NY 11747
1-800-645-7492

L/VIST32FB/D | AF | 02/22
© 2022 Resideo Technologies, Inc.
All rights reserved.